

Appl. No. 10/034,227
Amdt. dated March 15, 2005
Reply to Office action of December 15, 2004

Amendments to the Specification:

Please replace paragraph [0004] with the following amended paragraph:

[0004] When measured by a current flowing parallel to axis 123, the The resistance of the memory cell 120 differs according to the relative orientations of M1 and M2. When M1 and M2 are anti-parallel (e.g., the logic "0" state), the resistance of the memory cell 120 is at its highest. On the other hand, the resistance of the memory cell 120 is at its lowest when the orientations of M1 and M2 are parallel (e.g., the logic "1" state). Consequently, the logic state of the data bit stored in the memory cell 120 can be determined by measuring, either directly or indirectly, the resistance of the memory cell 120.

BEST AVAILABLE COPY

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.